



The power for your life

LITHIUM BATTERY

24V-100AH, 24V-200AH, 48V-100AH 48V-200AH 48V-300AH



Main Features

-  Supports wall mounted installation.
-  100A/150A Smart BMS matched well with solar system.
-  All around protection and unattended operation.
-  New LiFePO4 cells with competitive cost, super safety.
-  5 Years warranty, 6000+ cycles, 15 years life design.
-  Optional for multiple communication protocols for other brands of inverters.



MODEL	URL 24V-100AH Li-Wall series	URL 24V-200AH Li-Wall series	URL 48V-100AH Li-Wall series	URL 48V-200AH Li-Wall series	URL 48V-300AH Li-Wall series
Battery Type	LiFePO4	LiFePO4	LiFePO4	LiFePO4	LiFePO4
Total Energy	2560Wh	5120Wh	5120Wh	10240Wh	15360Wh
Usable Energy(80%DOD)	2048Wh	4096Wh	4096Wh	8192Wh	13824Wh
Voltage window	22.4~29.2V	22.4~29.2V	44.8~58.4V	44.8~58.4V	44.8~ 58.4V
Fast Charge Voltage	28.8V	28.8V	57.6V	57.6V	57.6V
Folat Charge Voltage	28.0V	28.0V	56.0V	56.0V	56.0V
Low DC Cut-off Voltage	23.4V	23.4V	46.8V	46.8V	46.8V
Max.continue discharge current	100A	150A	100A	150A	200A
Max.pulse discharge current	150A 1Sec.	200A 1Sec.	150A 1Sec.	200A 1Sec.	300A 1Sec.
Max.continue charge current	50A	100A	50A	100A	150A
Scalable	1~15 in parallel				
Communication	RS485				CAN ,RS485
Cycle life	>6000 Cycles@(+25°C,0.2C,90%DOD,60%EOL)				>8000 Cycles@ (+25°C,0.5C,90%DOD,60%EOL)
Terminal	M8				
Storage temperature	0°C~30°C				
Storage duration	6 months at 25°C				
Safety standard	UN38.3,MSDS				
IP degree	IP20				
PROTECTION					
Protection	Over charge protection, Over discharge protection, Over current protection, Shortcircuit protection, Over temperature protection				
AMBIENT					
Working Temperature	-10°C~+50°C				
Humidity	0~95% (no condensation)				
DIMENSION					
LxWxH (products size) mm	440*375*170mm	565*375*180mm	565*375*180mm	690*570*177mm	900*625*190
LxWxH (package size) mm	486*424*211mm (UN carton)	615*425*211mm (UN carton)	615*425*211mm (UN carton)	780*630*355mm (UN wooden cases)	948*690*372 (UN wooden cases)
Weight(NW Kg)	26.2Kg	45.3Kg	45.6Kg	83Kg	122.7Kg
Weight(GW Kg)	27.8Kg	47.6Kg	47.9Kg	98Kg	143.3Kg

